



DATA SHEET

Efficient. Agile. Scalable.

Exos X 2U12 Advanced Storage Array



Seagate® Exos® X advanced storage array is a petabyte-scale, rack-mounted block storage enclosure with self-healing technology, advanced data protection, and software value delivering superefficient mass-capacity storage for conventional data centers and cloud infrastructure.



Product Highlights

- Self-healing storage technology, ADAPT, and ADR
- Deliver unfettered data access with dual redundant controllers capable of achieving superior sequential read and write performance
- Expand a data center seamlessly with flexible SSD, HDD, and hybrid configuration options
- Efficiently manage hot and cold data with real-time data tiering
- Save space and maximize capacity by stacking 10 Enclosures for 120 drives of data storage

Key Advantages

Reliable and Self-healing. Exos X features self-healing storage technology, Advanced Distributed Autonomic Protection Technology (ADAPT) and Autonomous Drive Regeneration (ADR). Field-proven design with five nines (99.999%) availability. Seagate ADAPT erasure code data protection software dramatically reduces array rebuild overhead. Unique Seagate ADR reduces human intervention and e-waste by automatically renewing hard drives "in situ" and on the fly.

Built for speed and resilience. Up to 2 times the performance of the previous generation with redundant active-active controllers powered by the ASIC-based VelosCT controller architecture. Streamline your overhead, with improved throughput, management, and recovery.

Easy to Set Up, Maintain, and Expand. All system components—the enclosure, the controller, the firmware, and the drives—are developed and optimized by our engineers to work together seamlessly. The modular architecture makes components interchangeable between systems, and upgrades are simple due to common FRUs, PCMs, controllers, and software.

Gain and Scale Capacity with Consistent High Performance. The Exos X 2U12 enables even the smallest business with maximum speed and throughput. Additionally, businesses can expand the system as data requirements grow, with 12 drive slots of storage capacity in a 2U rackmount enclosure. Connect up to ten 2U12 enclosures together for a total of 120 drive slots.

Build In Security at the Foundation of the Data Life Cycle. Protect the most valuable business assets with Seagate Secure™ cybersecurity features and intelligent firmware—such as SFTP, SED support, and administrator access controls—that provide built-in measures for reliable and safe file access, transfer, and management.

Improve Hardware and Administrative Efficiency and Reduce Cost. Meet stringent worldwide requirements for recycling and environmental friendliness with a nimble system that minimizes environmental impact and maximizes cost savings through high performance.



Specifications	
Controller Performance	Up to 12GB/s read throughput, 10GB/s write throughput, 725K IOPS (Random Read)
Advanced Software Features	Auto-Tiering, Snapshots, Asynchronous Replication
Base Array Software Features	Virtual pools, Thin provisioning, ADAPT, SSD read cache, Encryption
High-Availability Features	Self-healing storage with Advanced Distributed Autonomic Protection Technology (ADAPT) and Autonomous Drive Regeneration (ADR), redundant hot-swap controllers, drives, and fans, dual power cords, hot standby spare, automatic failover, and multi-path support.
Device (Drive) Support	SAS HDD, NL-SAS HDD, SAS SSD (2.5 or 3.5 Form Factors)
Data Protection	Seagate ADAPT and RAID levels supported: 0, 1, 5, 6, 10
Self Healing Technology	Autonomous Drive Regeneration (ADR)
System Maximum Expansion	2U12 Arrays, Up to 12 drives per enclosure, 10 enclosures maximum including the master, totaling 120 Drives 2U24 Arrays, Up to 24 drives per enclosure, 10 enclosures maximum including the master, totaling 240 Drives 5U84 Arrays, Up to 84 drives per enclosure, 4 enclosures maximum including the master, totaling 336 Drives
Physical	2U: Height: 87.9mm / 3.46 in, Width: 443mm / 17.44 in, Depth: 630mm / 24.8 in, Width w/ear mounts: 483mm / 19.01 in, Weight: 17kg / 38 lb, Weight (with drives): 30kg / 66 lb
Hosts	
External Ports	4 per Controller, 8 per System
Fibre Channel Models	Host speed: 32/16 Gb/s Fibre Channel, Interface type: SFP+/SFP28
iSCSI Models	Host speed: 10Gb/s, 25Gb/s iSCSI, Interface type: SFP+/SFP28
Ethernet	10GBASE-T (auto-negotiation to 1Gb)
SAS Models	Host speed: 12Gb/s, 6Gb/s SAS, Interface type: HD Mini-SAS
System Configuration	
System Memory	48GB per system
Volumes per System	1024
Cache	Mirrored cache, Supercapacitor cache backup, Cache backup to flash – nonvolatile
Management	
Interface Types	10/100/1000 Ethernet, Micro USB
Protocols Supported	SNMP, SSL, SSH, SMTP, HTTP(S), Redfish
Management Consoles	Web GUI, CLI
Management Software	Seagate Systems storage management console, Remote diagnostics, Nondisruptive updates, Volume expansion
Power Requirements—AC Input	
Input Power Requirements	100VAC-240VAC, 50Hz/60Hz
Max Power Output per PSU	580W
Environmental/Temperature Ranges	
Operating/Nonoperating Temperature	ASHRAE A2, 5°C to 35°C (41°F to 95°F), derate 1°C/300m above 900m, 20°C/hr max rate of change / -40°C to 70°C (-40°F to 158°F)
Operating/Nonoperating Humidity	-12°C DP and 8% RH to 21°C DP and 80% RH, max DP 21°C / 5% to 100% noncondensing
Operating/Nonoperating Shock	5 Gs, 11ms, half sine pulses / 15 Gs, 7ms, half sine pulses
Operating/Nonoperating Vibration	0.18 Gs rms 6Hz to 500Hz random / 0.5 (Z-axis) and 0.25 (X&Y-axis) Gs rms 6Hz to 200Hz random